


Ultimo HS



Description

The Easy-Trim Ultimo HS breather membrane is a five layer heavy duty breather membrane, designed with an intelligent fleece-back technology to ensure the possibilities of condensation are eradicated when installed. The Ultimo HS breather membrane is designed to deal with high levels of moisture, similar to those experienced during the drying out of the buildings. The membrane absorbs and releases the moisture in a systemic way to prevent water droplets forming behind the membrane. This alleviates any risk associated with the condensation.

The Ultimo HS breather membrane, like all other breather membranes within the range, acts as a secondary barrier to prevent wind driven rain, snow and dust penetrating into the roof space below.

Suitable for applications on warm, cold and hybrid roofs, together with Scottish sarking boards, and equally applicable for installations in timber and metal framed constructions.

Benefits

- BBA certified for warm and cold roof applications BBA 10/4753
- Conforms to BS5534.2014 Annex A
- Superior strength
- 5 layers with reinforcement
- Flee-back Highly intelligent membrane performance
- UV stable for 3 months
- Type LR Underlay to BS5250
- Vapour permeable

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk



Ultimo HS

Product Data

Properties	Method	Units	Nominal Values	Tolerances	
				Minimum	Maximum
Length	EN 1848-2	[m]	30m	-	-
Width	EN 1848-2	[m]	1m	-0,0075	+0,0225
Straightness	EN 1848-2	-	conforming	-	-
Mass per unit area	EN 1849-2	[g/m ²]	270	-20	+20
Visible defects	EN 1850-2	-	Without visible defects	Without visible defects	
Reaction to fire	EN 13501 EN 11925-2	[class]	E	-	-
Resistance to water penetration	EN 1928 EN 13111	[class]	W1	-	-
Resistance to water penetration after artificial ageing	EN 13859-1 Annex C	[class]	W1	-	-
Water vapour transmission properties (Sd)	EN 12572 EN 1931	[m]	0,03	-0,02	+0,015
Tensile properties: Maximum tensile force MD / CD	EN 12311-1 EN 13859-1	[N/50mm]	600/700	-100 / -150	+100 / +150
Max tensile force after artificial ageing MD / CMD	EN 13859-1 Annex C	[N/50mm]	570/670	-100 / -150	+110 / +160
Tensile properties: Elongation MD / CMD	EN 12311-1 EN 13859-1	[%]	45/30	-25 / -15	+20 / +20
Elongation after artificial ageing MD / CMD	EN 13859-1 Annex C	[%]	40/30	-22 / -17	+20 / +15
Resistance to tearing MD / CMD	EN 12310-1 EN 13859-1	[N]	750/650	-150 / -150	+100 / +100
Dimensional stability	EN 1107-2	[%]	<2	-	-
Flexibility at low temperature	EN 1109 EN 495-5	[°C]	-20	-	-
Resistance to penetration of air	EN 12114 EN 13859-1	[m ³ /m ² .h.50Pa]	npd	-	-
Temperature resistance	-	[°C]	-40 / +80	-	-
Hydrostatic pressure test	EN 20811	[cm]	>500	-	-

Notes: MD - Machine Direction, CMD - Cross Machine Direction, NPD - No performance determined.

Installation Guide

All Easy-Trim breather membranes are suitable for installations on all major pitch roofing and timber frame applications, and must be installed in accordance with our fixing instructions, complying with the recommendations of BS5534: 2014 + A1: 2015; BS5250: 2011 and BS8000-0: 2014 and any other applicable standard.

The products are designed to be installed by competent and experienced installers of slates and tiles.

Install Easy-Trim breather membranes by rolling out the membrane horizontally across the rafters going from left to right, with a 100mm lap over the pre-installed Easy-Trim felt support trays at the eaves (preferably taped with the double sided overlap tape). Ensure the membrane is installed with the printed side facing out.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
 Altham Industrial Estate | Altham
 Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk



Ultimo HS

Installation Guide - Continued

Continue with the next row above that, maintaining the prescribed horizontal and vertical laps in the table below, over the lower membrane.

Roof Pitch (°)	Horizontal Laps (mm)		Vertical Laps (mm)
	Not fully Supported	Fully Supported	
12.5 - 14	225	150	100
15 - 34	150	100	100
35 - 75	100	75	100

Horizontal laps in the underlay should be taped with the double sided overlap tape, or battened over and where possible the lap of the underlay should coincide with closest tiling or slating batten. Vertical laps should have a 100mm lap min and positioned above a rafter.

Ventilated Ridge: For ventilation at the ridge, the membrane should be stopped about 5 – 30mm from the apex of the roof, to achieve the recommended 5000mm/msq ventilation with the Easy Ridge F universal ridge kit installed.

Non Ventilated Ridge: In this application ensure a 150mm overlap of the membrane across the apex of the roof on both sides, before installing the Easy Ridge F universal ridge kit. Please refer to our BBA certificate for further reference.

Supported: All Easy-Trim breather membranes are suitable for use in fully supported applications. Please refer to our BBA certificate for further reference.

When fully supported on sarking sheathing, the products have adequate support to withstand wind uplift in all wind zones. Such applications include, installations over e.g. plywood, OSB boards and insulation for warm roof designs.

Unsupported: All Easy-Trim breather membranes are suitable for use within the geographical wind zones stated in table three of our BBA Cert. 10/4753.

Accessories

Overlap tape, membrane repair tape, felt support trays.

Packaging Information

Product	Code	Size	Pallet Quantity
Ultimo HS 265gsm	ULTIMOHS1	1m x 30m	30

Disclaimer

The information relates only to this specified material and may not be valid for such materials used in combinations with other materials and processes. This information is, to the best of the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of the information on the material for their own particular use.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
 Altham Industrial Estate | Altham
 Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:

