

## Easy Vent U - Lowline Slate Ventilators Pin Seal



# easy-trim Ventilation

### Slate Low-Line Ventilator (500 x 250mm) Pin Seal Low-Line Ventilator (600 x 300mm) Pin Seal

#### Description

The Easy-Vent U 'Low Line' ventilators have been designed to be both unobtrusive and practical. The 10k ventilation area is recessed within the profile and has no sharp edges to trap leaves and any other debris, significantly reducing the risk of blocked ventilation. Suitable for pitches of 22.5° and above.

#### Features

- UV Stable HIPS sheet with a 'pin-seal' finish
- Suitable for use with pitches of 22.5° and above
- Recommended 4mm flyscreen protection
- Comply fully with the requirements of NHBC, BS 5250:2002 and BR Document C
- Ventilation area 10,000mm<sup>2</sup>

#### Airflow resistance

##### Resistance when used as an extract terminal

10Pa	54m <sup>3</sup> /hr	(15 litres/sec)
42Pa	108m <sup>3</sup> /hr	(30 litres/sec)
162Pa	216m <sup>3</sup> /hr	(60 litres/sec)

#### Spacing centres required to achieve a ventilation area of:

- 5mm continuous opening - install at 2.0m centres
- 110mm continuous opening - install at 1.0m centres

#### Adapter required

Square to round pipe adapter to suit 110mm flexi-pipe.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive  
Altham Industrial Estate | Altham  
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:

