

Easy Vent U - Raised Cowl Slate Tile Ventilators



easy-trim Ventilation

Description:

The Easy Vent U 'Plain Tile' ventilator is an injected moulded product offering precision and strength. The ventilation area has no sharp edges to trap leaves and any other debris, significantly reducing the risk of blocked ventilation. They are designed to suit all plain tiles to BS402 part 1 and can be fitted without cutting the tiling battens. Suitable for pitches of 30° and above.

Features:

- Moulded in 'High Impact Polystyrene'
- UV Acrylic paint finish to suit most colours
- Suitable for use with pitches of 30° and above.
- Ventilation area 7,500mm²

Airflow Resistance:

Resistance when used as an extract terminal		
10Pa	54m ³ /hr	(15litres/sec)
42Pa	108m ³ /hr	(30litres/sec)
162Pa	216m ³ /hr	(60litres/sec)

Spacing centres required to achieve a ventilation area of:

- 5000mm²/m 1.5m
- 10000mm²/m 0.75m

Adapter required:

Rectangle to round pipe adapter to suit 110mm flexi-pipe

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:

