

Easy Vent U - Lowline Tile Ventilators



easy-trim Ventilation

Description

The Easy-Vent U 'Low Line' ventilators have been designed to be both unobtrusive and practical. The 10k ventilation area is recessed within the profile and has no sharp edges to trap leaves and any other debris, significantly reducing the risk of blocked ventilation. Suitable for pitches of 22.5 and above.

Features

- Moulded in 'High Impact Polystyrene'
- UV Acrylic paint to match most tile profiles and finishes
- Suitable for use with pitches of 22.5 and above
- Comply fully with the requirements of NHBC, BS 5250:2002 and BR Document C
- Recommended 4mm flyscreen protection
- Ventilation area 10,000mm²

Airflow resistance

Resistance when used as an extract terminal		
10Pa	54m ³ /hr	(15 litres/sec)
42Pa	108m ³ /hr	(30 litres/sec)
162Pa	216m ³ /hr	(60 litres/sec)

Spacing centres required to achieve a ventilation area of:

- 5000mm²/m 2.0m
- 10000mm²/m 1.0m

Adapter required

Square to round pipe adapter to suit 110mm flexi-pipe.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England
w: www.easy-trim.co.uk

find us:

