

## Quick Quilt

# Quick Quilt

### Description

Foil based insulation with recycled wadding.

### Composition

5 layer construction.

Outer layer: foil supported by spun bonded polypropylene.

Inner layers: reflective foil and recycled wadding.

Properties	Standard	Unit
Length		10m
Width		1.2m
Thickness		Nominal 33mm
Roll Weight		7kg
Roll Coverage		12m <sup>2</sup>
Thermal performance	BS EN16012	0.83m <sup>2</sup> k/w
Emissivity of outer layer	BS EN16012	0.07
Flammability	BS EN13501-1	Class U
Values below based on testing a single outer layer (There are 2 layers in product)		
Nail tear resistance	EN12310-1	130/150N (MD/CD)
Tensile strength	EN12311-1	230/220 N/50mm (MD/CD)
Elongation	EN12311-1	30/40% (MD/CD)

All information and data given according to the best of our knowledge. No warranty claims can be based on this data and information. We reserve the right to make technical modifications, in regards to product improvement or due to changes in our manufacturing process.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive  
Altham Industrial Estate | Altham  
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

