

Bitumen Primer



easy-trim[®] WeatherProofing

Description

A cold applied bituminous solution designed to penetrate and seal porous surfaces prior to the application of covering materials. Conforms to BS Code of Practice 144, Part 3.

Uses

EASY-TRIM BITUMEN PRIMER seals porous substrates and encourages the adhesion of bituminous waterproofing systems and sheet coverings. It may be applied successfully to a wide range of surfaces:

- Concrete
- Asbestos cement
- Slate
- Metals - mild steel, zinc, lead
- Lightweight concrete screeds.

Product Data

Colour:	Black
Coverage:	The application of BITUMEN PRIMER varies according to the porosity of the surface:
Metal Surfaces:	6 - 11m ² per litre
Concrete:	3 - 4m ² per litre
Bituminous:	5 - 8m ² per litre
Drying Time:	Allow to dry completely before installation begins. Drying time is dependant on ambient temperature, atmospheric conditions and porosity of substate, but the product can be completely dry between 2-6 hours at 20°C

Method of Use

Apply by brush or spray

Surfaces should be clean, ie. free from all oil, grease, dirt, dust and loose debris. On metal surfaces all loose rust should be removed using a wire bristled brush and where advanced signs of corrosion are evident these areas should initially be treated with a rust inhibitor such as red lead. Surfaces should preferably be dry although EASY-TRIM BITUMEN PRIMER will adhere to damp but not wet surfaces. EASY-TRIM BITUMEN PRIMER should be applied evenly across the surface in one generous coating.

Cleaning of Tools

Tools may be cleaned with paraffin or white spirit. Spillages should be wiped off surfaces before the compound has set.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:



Bitumen Primer

Storage

Indefinite in undamaged, tightly sealed containers.

Packaging

Available in 5 litre and 25 litre containers.

Handling

Wear recommended basic personal protection equipment.

We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

