

Cloak Board



Description

Cloak Boards have been used over the years in traditional method of achieving weather tightness along the verge on pitch roofs. The highly durable Cloak boards are installed to provide adequate support to the mortar bedding.

Uses

Verge undercloak, soffit strip

Benefits

- Highly Durable
- Available in various sizes
- Ensures a weathertight verge

Product Data

Colour: Buff
Composition: Manufactured from autoclaved fibre cement with a smooth upper surface

Method of Use

Install the cloak board along the length of the last rafter at the gable end from eaves to ridge. Carefully apply mortar to the gap between the roof covering and the cloak board, covering the battens as you go from eaves to ridge. At the ridge, ensure a continuous bed of mortar up to the ridge tile, linking through to the other verge.

Fire Performance

BS 476:Part 6:1989 I < 12, BS 476: Part 7:1997 class 1

Packaging Information

Product	Code	Size	Pallet Quantity
Cloakboard	Cloakboard	3.2mm x 1200mm x 150mm	1000pcs
Cloakboard 1.2m	Cloakboard1.2	4.5mm x 1200mm x 150mm	600pcs
Cloakboard 2.4m	Cloakboard2.4	4.5mm x 2400mm x 150mm	420pcs

Tel: +44 (0) 845 034 6008

e: enquiries@easy-trim.co.uk

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive
Altham Industrial Estate | Altham
Lancashire | BB5 5TU | England

w: www.easy-trim.co.uk

find us:

