

## PolyureCoat



# easy-trim<sup>®</sup> WaterProofing

### Description

PolyureCoat is a liquid waterproof membrane, formulated from a unique blend of moisture triggered polyurethane resin to produce a fast curing, seamless, tough and elastic waterproofing system. Highly durable and puncture resistant. Ideal for both new construction and refurbishment projects.

### Advantages

- Solvent free
- Low odour system
- Suitable for applications on both new and refurbishment projects, and commercial roofs.
- Applicable in temperatures as low as 5°C
- Applicable on existing bitumen felt, existing asphalt, concrete, GRP, single ply (PVC) membranes and metal surfaces.

### Application

For application guidance please refer to our separate document or visit [www.polyurecoat.co.uk](http://www.polyurecoat.co.uk)

### Suitable for installations on

- New build and refurbishment projects
- GRP Roofs
- Profiled metal roofs
- Existing Single ply membrane (PVC)
- Existing Bituminous felt
- Existing Mastic Asphalt
- Concrete deck
- New Ply/OSB decks
- Large Commercial roofs
- Metal & Plywood Gutters

Tel: +44 (0) 845 034 6008

e: [enquiries@easy-trim.co.uk](mailto:enquiries@easy-trim.co.uk)

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive  
Altham Industrial Estate | Altham  
Lancashire | BB5 5TU | England

w: [www.easy-trim.co.uk](http://www.easy-trim.co.uk)

find us:



## PolyureCoat

### Typical Physical & Performance Data

<b>Packaging</b>	6kg and 25kg tins
<b>Application</b>	Roller
<b>Colours</b>	Dark grey
<b>Pallet Quantity</b>	6kg - 80 tins 25kg - 36 tins
<b>Colours</b>	Dark grey
<b>Storage</b>	12 months in original, unopened and tightly closed containers, at temperature 5°C to 20°C Please refer to Safety Datasheets.

### Guarantees

<b>15 year guarantee</b>	1.7kg/m <sup>2</sup> applied in 2 coats
<b>20 year guarantee</b>	2kg/m <sup>2</sup> applied in 2 coats

### Related Products & Accessories

Easy-Trim Reinforcing Fleece  
Easy-Trim GFR Matting  
GRP Trims  
PolyureCoat Accelerator - 210ml (6kg) and 850ml (25kg)

### Disclaimer

The information relates only to this specified material and may not be valid for such materials used in combinations with other materials and processes. This information is, to the best of the Company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of the information on the material for their own particular use.

Tel: +44 (0) 845 034 6008

e: [enquiries@easy-trim.co.uk](mailto:enquiries@easy-trim.co.uk)

f: +44 (0) 845 034 6010

Unit 12B Metcalf Drive  
Altham Industrial Estate | Altham  
Lancashire | BB5 5TU | England

w: [www.easy-trim.co.uk](http://www.easy-trim.co.uk)

find us:

